



15K-2P

Spec Sheet



Battery (optional) Output Power 12000W	
Type	Lead-Acid or Li-Ion
Nominal DC Input	48V
Capacity	50 — 9900Ah
Voltage Range	43.0 — 63.0V
Continuous Battery Charging Output	275A
Charging Curve	3-Stage w/ Equalization
Grid to Batt Charging Efficiency	96.0%
External Temperature Sensor	Included
Current Shunt for Accurate % SOC	Integrated
External Gen Start Based on Voltage or %SOC	Integrated
Communication to Lithium Battery	CanBus & RS485

Solar Input Power 19000W	
Max Allowed PV Power	19000W
Max PV Power Delivered to Battery & AC Outputs	15000W
Max DC Voltage (Voc)	500V @ 26A
MPPT Voltage Range	150-425V
Starting Voltage	125V
Number of MPPT	3
Max Solar Strings Per MPPT	2
Max DC Current per MPPT (Self Limiting)	26A
Max AC Coupled Input (Micro/String Inverters)	19200W

General	
Dimensions (H x W x D)	31.8" x 18.3" x 10.9"
Weight	135 lbs
Enclosure	IP65 / NEMA 3R
Ambient Temperature	-40~60°C, >45°C Derating
Installation Style	Wall-Mounted
Wi-Fi & LAN Communication	Included
Standard Warranty (verified by HALT Testing)	10 Years

AC Output Power 15kW On-Grid & Off-Grid	
Connections	120/240/208V Split Phase
Continuous AC Power with PV	15000W 62.5A-L (240V)
Continuous AC Power from Batteries	12000W 50A-L (240V)
Surge AC Power 10sec	18000VA L-L (240V)
Surge AC Power 100ms	22500VA L-L (240V)
Total Harmonic Distortion (THD)	Less Than or Equal to 3%
Parallel Stacking	Yes - Up to 12
Frequency	60/50Hz
Continuous AC Power with Grid or Generator	48000W 200A L-L (240V) 24000W 200A L-N (120V)
CEC Efficiency	96.5% (Peak 97.5%)
Idle Consumption Typical—No Load	90W
Sell Back Power Modes	Limited to Household/Fully Grid-Tied
Design (DC to AC)	Transformerless DC
Response Time (Grid-Tied to Off-Grid)	5ms
Power Factor	+/- 0.9 - 1.0

Protections & Certifications	
Electronics Certified Safety by SGS Labs to NEC & UL Specs - NEC 690.4B & NEC 705.4/6	Yes
Grid Sell Back — UL1741-2010/2018, IEE-E1547a-2003/2014, FCC 15 Class B, UL1741SA, CA Rule 21, HECO Rule 14H	Yes
PV DC Disconnect Switch — NEC 240.15	Integrated
Ground Fault Detection — NEC 690.5	Integrated
PV Rapid Shutdown Control — NEC 690.12	Integrated
PV Arc Fault Detection — NEC 690.11	Integrated
PV Input Lightning Protection	Integrated
PV String Input Reverse Polarity Protection	Integrated
AC Output Breakers - 200A	Integrated
2 x 200A Battery Breaker / Disconnect	Integrated
Surge Protection	DC Type II / AC Type II

Design Type	DC Transformerless							AC Coupled	
	Sol-Ark 15K	Sol-Ark 12K	Sol-Ark 8K	Sol-Ark 5K	Generac PWRcell 7.6 +4x\$2500	SolarEdge Energy Hub 7.6 32xP400	Panasonic (Darfon) 2xH5001	Enphase 2x10 +36xIQ7P	Tesla 2x Powerwall2 + String Inv
Brand & Model									
MSRP Price	\$8,000	\$6,900	\$6,100	\$4,500	\$6,500	\$7,600	\$6,200	\$28,440	\$20,600
Solar PV <i>Continuous Power</i>	16KW	12KW	9KW	6.5KW	11KW	7.6KW	2x6KW	10.4KW	12KW
Inverter AC Continuous Power	15KW	9KW	8KW	5KW	7.6KW	7.6KW	2x5KW	10.4KW	2x5KW
Inverter Battery Continuous Power	12KW	9KW	8KW	5KW	9KW	6.1KW	2x5.5KW	2x3.8KW	2x5KW
Off Grid Inverter AC <i>Peak Power</i> (5s)	24KW	16KW	16KW	16KW	12KW	6.9KW	13KW	8.8KW	14KW
System Idle Power	90W	60W	60W	60W			200W		78W
AC to DC Charger	250A	185A	185A	120A	6.7KW	5KW?	120A	N/A	N/A
<i>User Interface</i>	color touch	color touch	color touch	color touch	Text	Text	Text	X	X
PV to Batt Efficiency @ 65%	97.5%	97.5%	97.5%	97.5%	92.0%	92.5%	91.0%	92.0%	92.5%
AC to Batt Efficiency @ 65%	96.0%	96.0%	96.0%	96.0%	93.0%	93.5%	90.0%	95.0%	95.0%
Batt to AC Efficiency @ 65%	95.5%	95.5%	95.5%	95.5%	93.0%	93.5%	90.0%	95.0%	95.0%
On Grid PV to <i>AC Efficiency</i> @ CEC	96.5%	96.5%	96.5%	96.5%	95.5%	98.0%	95.5%	97.0%	97.0%
<i>Time of Use or Off Grid</i>									
PV -> Batt -> AC <i>Losses</i> @ 65%	7%	7%	7%	7%	15%	14%	19%	13%	13%
Grid Failure <i>UPS Transfer Time</i>	5ms	4ms	4ms	4ms	1000ms	3000ms	20ms	20ms	2000ms
Low Cost Easy Install	✓	✓	✓	✓	✓	✓	✓	✓	✓
<i>Warranty</i>	10 yr	10 yr	5/10 yr	5 yr	10 yr	12/20/25 yr	10 yr	10 yr	10 yr
<i>AC Coupling</i> to existing Inverters	✓	✓	✓	✓	X	✓	✓	✓	✓
<i>Parallel Stacking</i>	✓	✓	X	X	X	✓	✓	✓	✓
<i>120/240/208V 3Phase</i>	✓	✓	X	X	✓	X	X	X	✓
Generator Charging	✓	✓	✓	✓	X	X	X	X	X
AC Load Shedding for TOU & Off Grid	✓	✓	✓	✓	✓	X	X	X	X
California & HECO (Grid Sell)	✓	✓	✓	X	✓	✓	✓	✓	✓
NEC UL1699B Arc Fault	✓	✓	✓	✓	✓	✓	X	✓	✓
Outdoor Enclosure	✓	✓	✓	✓	✓	✓	X	✓	✓
Battery Bank	20KWh 6000cycles +\$13K	20KWh 6000cycles +\$13K	20KWh + \$13K	20KWh + \$13K	18KWh 3500c +\$13K	2x9.8KWh 3000c +\$12K	18KWh 3000c +\$15K	21.0KWh 6000cycles	28KWh 3500cycles